

## TENNIS BACKBOARDS

Effective January 1, 2004

### Premier TRAINER Series

#### 8' High System    10' High Systems



#### **TRAINER 1200**

- 12' wide x 8' high,
- 3-panels;



#### **TRAINER 1610**

- 16' wide x 10' high,
- 4-panels;



#### **TRAINER 1600**

- 16' wide x 8' high,
- 4-panels;



#### **TRAINER 2010**

- 20' wide x 10' high,
- 5-panels;



#### **TRAINER 2000**

- 20' wide x 8' high,
- 5-panels;



#### **TRAINER 2410**

- 24' wide x 10' high,
- 6 panels;


**INCLUDES:** High performance, flat FORTON MG panels with backslope, sound reduction, and a 4' high catch-net to keep high balls in play. Custom Sizes available.

### Economy ABS Series



#### **ABS 800**

- 8' wide x 8' high, 2-panels;



#### **ABS 1600**

- 16' wide x 8' high, 4-panels;



#### **ABS 1200**

- 12' wide x 8' high, 3-panels;



#### **ABS 2000**

- 20' wide x 8' high, 5-panels;

**INCLUDES:** High performance, flat ABS panels with backslope, sound reduction and a 4' high catch-net to keep high balls in play.

### Options



**Mobile Adapter Kit** - for easy set-up and transportation for 12' systems.

- TRAINER 1200/ ABS 1200

*(Trailer, Trainer 1200, ABS 1200, and 12V car battery not included)*

**Basic Installation** - Mobile Adapter Kit installed with new system

**Upgrade Installation** - installation to existing installed system

**Leasing & Prices Available- Call for Details**

## **TERMS AND CONDITIONS - *Tennis Backboards***

Effective January 1, 2004

- USA and Canada -

1. All prices are FOB Carpinteria, CA and are subject to change without notice.
2. **Shipping:**  
Drop shipments via Express truck to any location within the US.
3. **Payment Terms:**  
Payment terms are pre-pay or COD. Major credit cards are also accepted.
4. **Warranty:**  
ABS components are supplied with a three (3) year limited warranty. FORTON MG components are supplied with a five (5) year limited warranty.
5. **Site Location and Preparation:**  
Purchaser is responsible for providing the following prior to installation:
  - Flat, level surface;
  - Necessary support posts (2-3) or wall to which the Sportwall Tennis Backboard is attached to (Sportwall International Inc. offers a Base/Pole Kit for the Tennis 800 and the Tennis 1200 model that can be bolted into a concrete surface if you do not have existing fence posts or a wall available for installation.) - *if applicable*;
  - Filler material (~220lbs **dry** sand per panel).

Surface:

A concrete or asphalt base is recommended unless the Sportwall Tennis Backboard is being installed on a regulation tennis or sport court surface.

Support Posts:

The support posts to which the Sportwall Tennis Backboard is attached must be approximately 8' apart, 8' high and 2-1/2" to 3" Schedule 40 steel. The foundation for the posts should be 2' diameter and 3-1/2' deep in order to withstand a 75 m.p.h. frontal wind. Regulation tennis court fence posts work fine.

Location:

In exposed areas subject to high winds, it is advisable to locate the Sportwall Tennis Backboard side-on to the prevailing wind. Please consult an engineer for instructions on how to install the support posts to adequately carry the wind load in your area.

6. **Installation of Sportwall Tennis Backboards:**

# Sportwall International Inc.

1-805-745-5559 PHONE

805-745-1021 FAX

*sales@sportwall.com*

Installation instructions are supplied with each model. An average installation takes two adults approximately 2-4 hours. Sportwall International Inc. takes no responsibility for the quality of installation work done by the purchaser or any third parties contracted by the purchaser to install any Sportwall International Inc. product.